



KEY FEATURES

- Output Voltage: 0 – 5000 VDC (Adjustable)
- Output Power: 100 W to 2000 W (See table)
- High Efficiency & Low Ripple
- Precise Regulation & Low Noise
- Over Voltage, Over Current & Short Circuit Protection
- Output Enable / Disable & Interlock
- Local Control, Analog & Digital Remote Control
- HV ON Indicator & Fault Indication
- High Isolation & Safety

AVAILABLE MODELS

MODEL	MAX OUTPUT POWER	MAX OUTPUT CURRENT	OUTPUT VOLTAGE
HVPS-100-5000	100 W	20 mA	0 – 5000 VDC
HVPS-250-5000	250 W	50 mA	
HVPS-500-5000	500 W	100 mA	
HVPS-1K-5000	1000 W	200 mA	
HVPS-2K-5000	2000 W	400 mA	

CUSTOM OUTPUT CURRENT / POWER
AVAILABLE ON REQUEST

TYPICAL APPLICATIONS



HIGH VOLTAGE ISOLATION
Up to 10 kV Isolation



RELIABLE & PRECISE
Stable Performance with Low Ripple & Noise



RUGGED INDUSTRIAL DESIGN
Built for Continuous Operation



GLOBAL SAFETY STANDARDS
Designed to Meet International Standards

